

Winter-damage in Porous Asphalt Designing a binder solution using Kraton™ polymers

A Delft University of Technology study concluded that two factors are critical to prevent winter damage:

- Limited binder stiffness at low temperature, particularly after ageing;
- Binder stress relaxation at these low temperatures.

A few cold winter nights can cause years' worth of ravelling damage to a road when stresses due to traffic loads and day to night temperature variations reach the binder's breaking point.

Mortars of long-lasting, porous asphalt roads were compared in the lab to those from early-failure roads. A Finite Element model, that predicted the asphalt mix response based on the mortar properties, confirmed actual road performance and generated these conclusions.

Delft University of Technology in The Netherlands and Kraton Performance Polymers, Inc., headquartered in the USA, used proven knowledge of SBS polymers to tune and enhance the binder's visco-elastic properties over a wide temperature range to formulate a superior, winter-damage resistant binder. Delft University aged and tested four different Kraton binders and modelled their winter performance, all showing a dramatic improvement in particular in ravelling resistance. The Kraton polymer modified binders demonstrated exceptional performance in the winter and equally good performance under summer conditions.

Highly modified binders for porous asphalt have a 20 year track record of durability in Japan with SBS levels typically at 8%, but as high as 11% in the coldest parts of the country. This evaluation reinforces that experience and highlights how to optimize formulations to eliminate winter ravelling damage.

Testing



Mortar testing: Material Response parameters, obtained from Dynamic Mechanical Analysis [C] on mortar [A] samples [B], were used as an input for the Finite Element Model.

Modeling



Porous Asphalt Modeling: Modelling of a pavement under dynamic loading.



Results: Days of winter service life. Computer modelling results of winter damage of extracted lab tested actual road binders and formulated aged binders at -10 °C (average temperatures and a day and night variation of 6 °C).





Kraton polymer based winter damage resistant binders do not compromise on high temperature performance.



Force Ductility [25 °C] measurements showing the dramatic difference in cohesive strength and resilience between unmodified binder and Kraton hard (100 pen base) and soft (300 pen base) binders.

Kraton Performance Polymers, Inc. (NYSE:KRA)

Corporate Headquarters: 15710 John F. Kennedy Blvd., Suite 300 Houston, Texas 77032 Tel: +1-800-4-KRATON (572866)

Europe/Middle East/Africa: John M. Keynesplein 10 NL – 1066 EP Amsterdam The Netherlands Tel: +31 (0)20 201 7697 Asia Pacific: Rm 1601-03, Plaza 66, Phase 2 1266 West Nanjing Road Shanghai 200040, China +86 21 628<u>9 6161</u>_____

South America Av. Roberto Simonsem, 1500 13140-000 - Paulinia – SP, Brazil +55 19 3874 7270

Legal Disclaimer:

We believe the information set forth above to be true and accurate, but any recommendations, presentations, statements or suggestions that may be made in the foregoing text are without any warranty or guarantee whatsoever, and shall establish no legal duty on the part of Kraton Performance Polymers, Inc. or any of its affiliates. Furthermore, nothing set forth above shall be construed as a recommendation to use any product in conflict with any existing patent rights. Kraton Performance Polymers, Inc. expressly disclaims any and all liability for any damages or injuries arising out of any activities relating in any way to this publication.

(affiliation

Kraton and the Kraton logo are registered trademarks owned Kraton Performance Polymers, Inc.

Giving Innovators Their Edge is a registered service mark owned by Kraton Performance Polymers, Inc.